Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

	Supplier	's name o	r trade mark	: Kdln Srl
--	----------	-----------	--------------	------------

Supplier's address: ufficio tecnico, Viale Francesco Crispi 5, 20121 Milano Milano MI, IT

Model identifier: LED NAMI WALL - RO

_		•			
11/1	ഘ	Λt	liont	sourc	Ά.
	~	v	115111	3041	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	WIRE		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

Product parameters

Froduct parameters					
Parameter		Value	Parameter	Value	
	General product parameters:				
<u> </u>	nption in on- 00 h), rounded st integer	12	Energy efficiency class	E	
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	1 517 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode power (P _{on}), expressed in W		11,8	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90	
Outer dimen-	Height	15	Spectral power dis-	See image	
sions without	Width	98	tribution in the	in last page	
separate con- trol gear, light-	Depth	6	range 250 nm to 800 nm, at full-load		

ing control parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,458	
		nates (x and y)	0,409	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	50	Survival factor	0,98	
the lumen maintenance factor	0,97			

(a)'-': not applicable; (b)'-': not applicable;

