## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	Absolut Lighting
--------------------------------	------------------

Supplier's address: Verkauf, Hamburgerstraße 8a, 50321 Vochem Brühl Rhein-Erft-Kreis, DE

Model identifier: 457 LED (ABSOLUT / BASICA 2700K CRI>90)

_	•			
IVna	Λt	light	source	٠.
IVDC	vı	HEILL	Jource	- •

Type of light so	urce:			
Lighting techno	logy used:	LED	Non-directional or directional:	DLS
Light source cap	o-type	COB verklebt		
(or other electri	ic interface)	auf Kühlkörper		
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	Yes		
Anti-glare shield	d:	Yes	Dimmable:	Yes
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	arameters:	
	mption in on- 100 h), rounded st integer	9	Energy efficiency class	F
indicating if it r in a sphere (3 cone (120º) or i (90º)	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	845 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pressed in W	oower (P <sub>on</sub> ),	9,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
for CLS, expres	idby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer	Height	1	Spectral power	See image
dimensions	Width	15	distribution in the	in last page
without	Depth	12		

if any (millimetre)			
Claim of equivalent power <sup>(a)</sup> - If yes, equivalent - power (W)			
Chromaticity 0,421			
coordinates (x and y) 0,397			
Parameters for directional light sources:			
Peak luminous intensity (cd) 459 Beam angle in 85			
degrees, or the			
range of beam			
angles that can be			
set			
Parameters for LED and OLED light sources:			
R9 colour rendering index value 60 Survival factor -			
the lumen maintenance factor -			

(a)'-': not applicable; (b)'-': not applicable;

