

BUTTON

Lamps description : 1 x 22W 2GX13 T5 FSC + Environment : Indoor, Outdoor Finish : White, Blue, Yellow, Opal Technical description : Indoor and outdoor wall/ordiffused light. Slightly opal injection-molded polycarbors screw/diffuser support in chandpolished aluminum all liquid transparent paint. TI slightly, injection-molded plight bulb support is 30% on ylon, injection molded an		
Finish : White, Blue, Yellow, Opal Technical description : Indoor and outdoor wall/ordiffused light. Slightly opal injection-molded polycarbo screw/diffuser support in ordinary in the propertion of the properties of the properti	: 1 x 22W 2GX13 T5 FSC + 1 x 40W 2GX13 T5 FSC	
Technical description : Indoor and outdoor wall/or diffused light. Slightly opal injection-molded polycarbor screw/diffuser support in chandpolished aluminum all liquid transparent paint. The slightly, injection-molded plight bulb support is 30% of the support is		
diffused light. Slightly opal injection-molded polycarbo screw/diffuser support in change in the support in change in the support in the slightly, injection-molded plight bulb support is 30% of the support in	: White, Blue, Yellow, Opal	
Sílicone élastomer dust an	ne (PC opal), nate diffuser. Closure ie-cast and oy protected with e wall attachment is olycarbonate. The llass fiberreinforced d matte white.	

ELECTRICAL

Control gear availability	: Included
Control gear type	: Electronic
Emergency	: Without
Voltage (V)	: 230/240

PHYSICAL	
Shape	: Round
Supply	: Terminal block
Construction material	: Aluminum or Nylon or Polycarbonate
Weight (kg)	: 2,15





Button design by Piero Lissoni

Indoor and outdoor wall/ceiling lighting lamp providing diffused light

Reference Code	
F3180009 F3180014	White / White White / Blue White/Yellow
_L2100013	willte/ reliow
	○ F3180009





