	MB1	Mini gel box IP68		230V 230V 230V 0UT 12V	ED6CR	Driver 10W 1
		5,3x3,9x2,4 cm				230V and 12V
		(max 2 connections - connectors included)				3,7x2,3x7 cm
						not dimmable
				u di		(max 6 lamps
	MB2	Mini gel box IP68			CRM	Quick IP68 n
		5,2x5,3x2,9 cm				(max 5 connect
		(max 6 connections - connectors included)				
	KP1	Extension cord kit			CRS	Quick IP68 II
		5 mt				
		with mini gel box IP68 for single connection				
		(max 1 lamp)				
	ED6	Driver 10W 12V DC 220-240V IP67			KP2	Extension co
		7x3,7x2,3 cm / cables 45 cm ca.				5 mt
		not dimmable		OUT IN		(max 1 lamp)
		(max 6 lamps)				
	ED7	Driver 30W 12V DC 220-240V IP67			FKIPL	Kit box drive
		11x3,7x2,3 cm / cable 12V 45 cm ca. / plug cable 200 cm				Ø 5x20 cm /
		not dimmable				not dimmable
		(max 20 lamps)				standard
				~		
	ED7D	Driver 30W 12V DC 220-240V IP67			FKIPLD	Kit box drive
		8x8x3 cm / cables 12V 45 cm ca. / plug cable 200 cm				16x10x4 cm /
		Triac dimmable				Triac dimmab
		(max 20 lamps)				available on re
				<i>د</i>		

DW 12V DC 220-240V IP67 /
d 12V connectors included
7 cm - cables 45 cm ca.
nable
mps)
68 multiple connector / 1 IN & 5 OUT 12V
nnections)
68 IN single connector
on cord kit with quick IP68 connectors CRS
(qm
driver
cm / cable 12V 45 cm / plug cable 200 cm
nable (driver ED7)
driver

cm / cable 12V 45 cm / plug cable 200 cm


nable (driver ED7D)


on request

	MSMP	Supporting modular plate			
		for More (MR70/MR100/MR130)			
		32x32x32 cm	WARNING		
		(max 4 lamps)	For stability reasons the lamp must be fastened to a solid surface such as a well or basement; in alternative it can be mounted on the modular supporting plate (ref. L / code MSM) available on request. Before installing the lamp, please check the levelling of the soil and make sure that it can support the weight of the fitting.		
			(Medousê weight Ø 30 cm 15 kg / Ø 50 cm 31 kg)		
	MPT	Peg			
		for More (MR70/MR100/MR130)	Example 1		
		25 cm			
			with basement and supply cable from the side		
	MSM	Supporting plate	base		
		for Medousê F			
		31x31 cm ca.			
	MDCV	Plug cable 230V standard EU (CH available on request)	Example 2		
		for Medousê F	with well and supply cable from underneath		
		350 cm	base		

Example 3

with supporting plate 1x code MSM with plug cable 230V 1x code MDCV





lamp base with holes for the fastening (plugs not included)

