# **Starpoint** Pendant luminaires



# Illuminating tables for glamorous effect

Pendant luminaires for hotels, bars and restaurants

The Starpoint pendant luminaire combines the design principles of "ambient luminescence" and "play of brilliants" coined by Richard Kelly. The light beam, directed downwards, presents cuisine and cocktails on the tables and counters in the perfect light. The luminaire cover with its strikingly illuminated ring creates an effective eye-catcher. The translucent element, which is visible only when illuminated, makes for a subtle dec-

orative detail in the room – ideal for hotels, bars and restaurants. A chrome version adds a touch of mid-century glamour and lends itself to combination with rough materials such as wood or natural stone, thereby creating a compelling contrast.

# **Starpoint** Pendant luminaires





**Accentuation** Emphasis of objects produced by a wide light beam.





Pendant downlights Wide beam, rotationally symmetrical light distribution for the illumination of large areas from a short distance.

**LED module** 8W 600lm - 830lm Light distribution: Extra wide flood

# **Starpoint** Pendant luminaires



**Structure and characteristics**The features described here are typical of products in this range. Special versions may offer additional or varying features. A comprehensive description of the features of individual products can be found on our website. The direct links for quick access always take the same form:

www.erco.com/<article number>

Detailed information on the features is provided in the Program  ${\bf from}$ page 432.

- 1 ERCO lens systemMade of optical polymerLight distribution: extra wide flood

### 2 ERCO LED module

- High-power LEDs on metal-core PCB
- Light colours: warm white or neutral white

- 3 Translucent ring
  Optical cut-off 30°
  Polymer, clear, outside mirror-finish vaporised

- Anti-glare cone Optical cut-off 30°
- Polymer, black

### 4 Cylinder


- White (RAL9002), black or chrome Aluminium profile, powder-coated or chrome-plated

### 5 Control gear:

- Phase dimmable
- Dimming with external dimmers possible (trailing edge)

# 6 ERCO 3-circuit adapter or

- ceiling fixture with canopy White or black Connection cable, translucent, with strain relief



Decorative luminaire trim



 $\perp \downarrow \downarrow \downarrow \downarrow$ 


ERCO high-power LEDs



Excellent thermal management



Phase dimmable





**EMC-optimised** 



Different light colours




Different housing colours




# **Starpoint** Pendant luminaires – Luminaire arrangement

**Pendant downlights** Extra wide flood



Accentuation
For uniform ambient lighting, the spacing (d) between two Starpoint pendant downlights may be up to approximately 1.25 times the height (h) of the luminaire above the working plane.

Arrangement:  $d \le 1.25 \times h$ 



The wall offset should be half the luminaire spacing.

Arrangement: a = d / 2

