

## WALL SYSTEM MINIKELVIN FLEX REMOTE POWER SUPPLY

|                   |                                |
|-------------------|--------------------------------|
| Number of heads   | 1                              |
| Mounting          | Wall surface                   |
| Lamps description | Top LED 4W 216 lm 3000K CRI 85 |
| Voltage (V)       | 24                             |
| Environment       | Indoor                         |

### OPTICAL

|                             |            |
|-----------------------------|------------|
| Aiming                      | Adjustable |
| Light distribution symmetry | Symmetric  |
| Beam angle                  | 111°       |

### ELECTRICAL

|                          |                     |
|--------------------------|---------------------|
| Transformer availability | Separate item       |
| Transformer mounting     | Remote              |
| Transformer type         | Electronic dimmable |
| Emergency                | Without             |
| Insulation class         | Class III           |

### PHYSICAL

|                       |           |
|-----------------------|-----------|
| Construction material | Aluminium |
| Weight (kg)           | 0,28      |




### Wall System Minikelvin Flex Remote Power Supply

designed by Antonio Citterio

Diffuse illumination lighting device for installation flush with the wall with remote driver. ON/OFF switch with Soft Touch technology and light flow adjustment to 2 intensities (100% - 50% - 0%).

|            |        |
|------------|--------|
| ● F9478009 | White  |
| ● F9478057 | Chrome |
| ● F9478030 | Black  |



### CERTIFICATIONS

