

**Materials**

diffuser discs lined with leaf (disc Ø 120 cm with flying leaf), nickel base

Light source	mod. A LED board 24V DC / 7x6W / energy class A / lumen 4410 / K range 2600-2800 / CRI 80
	mod. B LED board 24V DC / 2x6W / energy class A / lumen 1260 / K range 2600-2800 / CRI 80
	mod. C LED board 24V DC / 7x6W / energy class A / lumen 4410 / K range 2600-2800 / CRI 80
	mod. D LED board 24V DC / 10x6W / energy class A / lumen 6300 / K range 2600-2800 / CRI 80
	mod. E LED board 24V DC / 4x6W / energy class A / lumen 2520 / K range 2600-2800 / CRI 80
	mod. F LED board 24V DC / 9x6W / energy class A / lumen 5670 / K range 2600-2800 / CRI 80
	mod. I LED board 24V DC / 5x6W / energy class A / lumen 3150 / K range 2600-2800 / CRI 80
Power supply	low voltage driver 24V DC 220-240V dimmable Triac (dimmable 1...10V or DALI version available on request)? (110V available on request)
Dimensions	rods H 145 cm variable (on request 300 cm) base Ø 21×10,5 H cm  mod. D discs Ø 120-80-50-30-18 cm weight 16 kg    mod. A discs Ø 80-50-30-18 cm weight 10 kg mod. B discs Ø 80-18 cm weight 6 kg mod. C discs Ø 120-80-50 cm weight 13 kg  mod. E discs Ø 50-30-18 cm weight 6 kg mod. F discs Ø 120-80-50-30 cm weight 15 kg mod. I discs Ø 80-50-30 cm weight 8 kg

Order code mod. A	MALD	mod. A / gold
	MALDAG	mod. A / silver
	MALDR	mod. A / copper

Order code mod. B	MBLD	mod. B / gold
	MBLDAG	mod. B / silver
	MBLDR	mod. B / copper

Order code mod. C	MCLD	mod. C / gold
	MCLDAG	mod. C / silver
	MCLDR	mod. C / copper

Order code mod. D	MDLD	mod. D / gold
	MDLDAG	mod. D / silver
	MDLDR	mod. D / copper

Order code mod. E	MELD	mod. E / gold
	MELDAG	mod. E / silver
	MELDR	mod. E / copper

Order code mod. F	MFLD	mod. F / gold
	MFLDAG	mod. F / silver
	MFDLDR	mod. F / copper

Order code mod. I	MILD	mod. I / gold
	MILDAG	mod. I / silver
	MILDR	mod. I / copper
