

References



I SSL LED DIM0-10V



I SSL LED DIMBT

Certificates



Class I

Dimmable:
120 - 277VBluetooth Dimming:
220 - 240V

Wood shade colours

- 20 Ivory White
- 21 Natural Cherry
- 22 Natural Beech
- 24 Yellow
- 25 Orange
- 26 Red
- 28 Blue
- 29 Grey
- 30 Turquoise
- 31 Chocolate
- 32 Pink




Components

**Top diffuser**
Black or White

Note: The standard top diffuser is white. Black is also available if you want no upward light diffusion.

Bottom diffuser
Matt satin acrylic**Metal canopy**
Brushed Nickel
34 x 11,5 x 5 cm**Electrical cable**


Transparent 2 m drop

**Steel cable**
2 x 2 m drop**Box size**
181 x 34 x 23 cm**Box volume**
0,142 m³**Weight**
Gross - 11,5 Kg
Net - 4,1 Kg**LED****Linear Module**
5 x 5,5 W 350mA**Energy class**

LED integrated

**Driver**ERP
1 unit - Ref. ESS040W-1400-24ERP
1 unit - Ref. ESS040W-1400-24
+
Bluetooth Control - CASAMBI / ELT
1 unit - Ref. CBU - ASD

Driver housed in canopy.

REF. I SSL LED 21
I-Club Slim

Details

Input Voltage	Luminous Flux *	CRI	Watt.	CCT	Lifetime (L70)
120 - 277V	1632 lm	90	25 W	3000 K	40000h
220 - 240V					

* Measurements taken using white shades, Veneer Ref: 20 Ivory White