Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark	: LED Technology
-------------------------------	------------------

Supplier's address: Quality manager, Piazza IV Novembre, 11, 20124 Milano MI, IT

Mode	l identifier:	LSCC435D
------	---------------	----------

T	- 6	10 - 1- 1		
IVna	α T	IIσnt	source:	,
IVDC	vı	HEILL	Jourte.	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Product parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
_ ·	nption in on- 00 h), rounded st integer	4	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	360 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pow pressed in W	ver (P _{on}), ex-	4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	98	Spectral power dis-	See image
sions without	Width	35	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	35	range 250 nm to 800 nm, at full-load	

parts and non-			
lighting con-			
trol parts, if			
any (millime-			
tre)			
Claim of equivalent power ^(a)	Yes	If yes, equivalent	33
· ·		power (W)	
		Chromaticity coordi-	0,465
		nates (x and y)	0,415
		riates (x and y)	0,415
Parameters for LED and OLED lig	ght sources:		
R9 colour rendering index value	2	Survival factor	0,90
the lumen maintenance factor	0,95		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,79	Colour consistency	3
	,	in McAdam ellipses	
Claims that an LED light source	_(b)	If yes then replace-	-
replaces a fluorescent light		ment claim (W)	
source without integrated bal-		(**,	
last of a particular wattage.			
Flicker metric (Pst LM)	0,0	Stroboscopic effect	0,1
		metric (SVM)	

(a)'-': not applicable; (b)'-': not applicable;

